

Technische Abmessungen

Wir weisen ausdrücklich darauf hin, dass alle Angaben ohne Gewähr sind!

DIN 7993 Runddraht-Sprengringe, A= für Wellen



S	t	D	Tol	g	G	Tol	r
4	0.8	3.1	+0.0 -0.2	1	3.2	±0.05	0.5
5	0.8	4.1		1	4.2		0.5
6	0.8	5.1		1	5.2		0.5
7	0.8	6.1	+0.0 -0.3	2	6.2		0.5
8	0.8	7.1		2	7.2		0.5
10	0.8	9.1		2	9.2		0.5
12	1.0	10.8	+0.0 -0.4	3	11.0		0.6
14	1.0	12.8		3	13.0		0.6
16	1.6	14.2		3	14.4		0.9
18	1.6	16.2		3	16.4	0.9	
20	2.0	17.7	+0.0 -0.5	3	18.0	±0.10	1.1
22	2.0	19.7		3	20.0		1.1
24	2.0	21.7		3	22.0		1.1
25	2.0	22.7		3	23.0		1.1
26	2.0	23.7		3	24.0		1.1
28	2.0	25.7		3	26.0		1.1
30	2.0	27.7		3	28.0		1.1
32	2.5	29.1	+0.0	4	29.5	1.4	

35	2.5	32.1	-0.6	4	32.5		1.4
38	2.5	35.1		4	35.5		1.4
40	2.5	37.1		4	37.5		1.4
42	2.5	39.0	+0.0 -0.8	4	39.5		1.4
45	2.5	42.0		4	42.5		1.4
48	2.5	45.0		4	45.5		1.4
50	2.5	47.0		4	47.5		1.4
55	3.2	51.1		4	51.8		±0.15
60	3.2	56.1	4	56.8	1.8		
65	3.2	61.1	4	61.8	1.8		
70	3.2	66.0	+0.0 -1.0	5	66.8	1.8	
75	3.2	71.0		5	71.8	1.8	
80	3.2	76.0		5	76.8	1.8	
85	3.2	81.0		5	81.8	1.8	
90	3.2	86.0		5	86.8	1.8	
95	3.2	91.0	+0.0 -1.2	5	91.8		1.8
100	3.2	95.8		5	96.8		1.8
105	3.2	100.8		5	101.8		1.8
110	3.2	105.8		5	106.8		1.8
115	3.2	110.8		5	111.8		1.8
120	3.2	115.8	5	116.8	1.8		
125	3.2	120.8	5	121.8	1.8		