

Technische Abmessungen

Wir weisen ausdrücklich darauf hin, dass alle Angaben ohne Gewähr sind!

DIN 7993 Runddraht-Sprengringe, B= für Bohrungen



Alle Angaben in mm

B	t	D	Tol	g	G	Tol	r
7	0.8	7.9	+0.3 -0.0	4	7.8	±0.05	0.5
8	0.8	8.9		4	8.8		0.5
10	0.8	10.9		4	10.8		0.5
12	1.0	13.2	+0.4 -0.0	6	13.0	±0.05	0.6
14	1.0	15.2		6	15.0		0.6
16	1.6	17.8		8	17.6		0.9
18	1.6	19.8		8	19.6		0.9
20	2.0	22.3	+0.5 -0.0	10	22.0	±0.1	1.1
22	2.0	24.3		10	24.0		1.1
24	2.0	26.3		10	26.0		1.1
25	2.0	27.3		10	27.0		1.1
26	2.0	28.3		10	28.0		1.1
28	2.0	30.3		10	30.0		1.1
30	2.0	32.3		10	32.0		1.1

32	2.5	34.9	+0.6 -0.0	12	34.5		1.4
35	2.5	37.9		12	37.5		1.4
38	2.5	40.9		12	40.5		1.4
40	2.5	42.9		12	42.5		1.4
42	2.5	45.0	+0.8 -0.0	16	44.5		1.4
45	2.5	48.0		16	47.5		1.4
48	2.5	51.0		16	50.5		1.4
50	2.5	53.0		16	52.5		1.4
55	3.2	58.9		20	58.2		±0.15
60	3.2	63.9	20	63.2	1.8		
65	3.2	68.9	20	68.2	1.8		
70	3.2	74.0	+1.2 -0.0	25	73.2	1.8	
75	3.2	79.0		25	78.2	1.8	
80	3.2	84.0	+1.0 -0.0	25	83.2		1.8
85	3.2	89.0		25	88.2		1.8
90	3.2	94.0		25	93.2		1.8
95	3.2	99.0		25	98.2		1.8
100	3.2	104.2	+1.2 -0.0	32	103.2		1.8
105	3.2	109.2		32	108.2		1.8
110	3.2	114.2		32	113.2		1.8
115	3.2	119.2		32	118.2		1.8
120	3.2	124.2		32	123.2		1.8
125	3.2	129.2		32	128.2		1.8